

EXIT DEVICE INSTALLATION INSTRUCTIONS

K-102 SWITCH KIT

VON DUPRIN MODEL 88 EXIT DEVICES

SWITCH MONITORS EGRESS BY PUSH BAR ACTIVATION OF EXIT DEVICE

ELECTRICAL SPECIFICATIONS

- SPDT MONITOR SWITCH
- CONTACT RATING: 4 AMP @ 250VAC

COLOR CODE FOR WIRES

- YELLOW WIRE: COMMON
- RED WIRE: NORMALLY OPEN
- GRAY WIRE: NORMALLY CLOSED

INSTALLATION INSTRUCTIONS

- STEP 1: REMOVE TWO SCREWS AND HOLD DOWN CLAMP (NOTE POSITION OF CLAMP, THE HIGH END IS POSITIONED TOWARD TOP OF HOUSING, THE SHORT END GOES TOWARDS THE BOTTOM).
- STEP 2: REMOVE SPRING MECHANISM FROM HOUSING. NEXT PLACE SWITCH ASSEMBLY INTO HOUSING AS SHOWN. CAREFULLY REPLACE THE SPRING MECHANISM BACK INTO HOUSING.
- STEP 3: REPLACE HOLD DOWN CLAMP WITH SCREWS REMOVED IN STEP 1. BEFORE FULLY TIGHTENING THE SCREWS, MAKE SURE SPRING MECHANISM IS ACTIVATING THE SWITCH. ADJUST BRACKET ASSEMBLY AS NECESSARY FOR PROPER SWITCH ACTIVATION THEN TIGHTEN SCREWS FULLY.

