

SERIES 1310 MORTISE KEY SWITCHES WITH AUDIBLE ALARM

COVERS THE FOLLOWING MODELS:

- 1310-5 KEYSWITCH DOUBLE GANG WITH AUDIBLE ALARM.
MOUNTS IN A DOUBLE GANG WALL MOUNT ELECTRICAL BOX.
SIZE 4" SQ. X 2-1/8" DEEP. (RACO #680 OR EQUIVALENT)
- 1310-5-2 KEYSWITCH WITH 2 STATUS INDICATORS (RED & GREEN), AND AUDIBLE ALARM.
MOUNTS IN A DOUBLE GANG WALL MOUNT ELECTRICAL BOX.
SIZE 4" SQ. X 2-1/8" DEEP. (RACO #680 OR EQUIVALENT)

ELECTRICAL SPECIFICATIONS

- MOMENTARY DPDT CONTACT CONFIGURATION
- CONTACTS RATED AT 1A @ 30VDC
- LED INDICATORS RATED AT 20mA @ 24VDC
- AUDIBLE ALARM RATED 3-16mA @ 4-28VDC (FILTERED),
TONE FREQUENCY: 2900Hz, SOUND INTENSITY: 64-76dB

MOMENTARY ACTION FUNCTION

- WHEN THE KEY IS TURNED TO THE CLOCKWISE POSITION, THE BLACK LEAD MAKES CONTACT WITH THE WHITE LEAD AND BREAKS CONTACT WITH THE RED LEAD; THE BROWN LEAD MAKES CONTACT WITH THE BLUE LEAD AND BREAKS CONTACT WITH THE YELLOW LEAD.
- WHEN THE KEY IS RETURNED TO THE NORMAL COUNTERCLOCKWISE POSITION, THE CONTACTS RETURN TO THEIR NORMAL POSITION.

RED WIRE - N.C. YELLOW WIRE - N.C.
BLACK WIRE - COM. BROWN WIRE - COM.
WHITE WIRE - N.O. BLUE WIRE - N.O.

AUDIBLE ALARM

THE AUDIBLE ALARM HAS POLARIZED WIRE LEADS
RED WIRE LEAD IS (+) POSITIVE AND BLACK WIRE LEAD IS (-) NEGATIVE.

RED/GREEN LED STATUS INDICATORS

RED LED LEADS ARE IDENTIFIED WITH A RED CABLE TIE, AND THE GREEN LED LEADS ARE IDENTIFIED WITH A GREEN CABLE TIE. RED WIRE LEADS ARE (+) POSITIVE AND BLACK WIRE LEADS ARE (-) NEGATIVE.



MODEL 1310-5-2
SHOWN

